



Standard Specification Sheet Model: MS3904 AREX-39
Chassis-mounting High-Level Signal Conditioner with Isolated Dual-output

OVERVIEW



This is chassis-mounting isolator with dual-output that converts high-level voltage or electric current input signal into any desired standard process signal.

- ▽ Anti-humid coatings on PCB are standard for improved environmental protection.
- ▽ Multiple installations on chassis provide ease of maintenance and high-density population.
- ▽ Self pop-up screws on chassis provide ease of wiring.
- ▽ Fuse on DC power line is installed standard.

ORDERING INFORMATION

Ordering Code	Standard Price
MS3904 1 8	OPEN

SPECIFICATIONS

POWER SECTION

Power Requirement	24V DC \pm 10%
Power Sensitivity	\pm 0.1% of span max. @10% variance
Power Line Fuse	300mA fuse is installed, (standard)
Power Consumption	45mA max.

INPUT SECTION

Input Signal (Specify at ① when ordering)	■ 1~5V DC	V1
	■ 0~1V DC	V4
	■ 0~5V DC	V5
	■ 0~10V DC	V6
	■ \pm 5V DC	W5
	■ \pm 10V DC	W6
	■ 4~20mA DC (Input resistor 250 Ω)	C1
Input Resistance	Voltage input: 1M Ω min. (1M Ω minimum without power) Current input: 250 Ω (Standard for 4~20mA)	
Allowable Input Voltage	Voltage input: 30V DC max. continuous Current input: 40mA DC max. continuous	

OUTPUT SECTION

Output Signal (Specify at ② when ordering)	OUT-1/OUT-2	Code
	■ 1~5V DC/1~5V DC	V1
	■ 0~5V DC/0~5V DC	V5
	■ 0~10V DC/0~10V DC	V6
	■ \pm 5V DC/ \pm 5V DC	W5
	■ \pm 10V DC/ \pm 10V DC	W6
	■ 1~5V DC/4~20mA DC	C1
Combinations of two output signals are limited to the above.		
Maximum Output Load	Voltage output: 2mA max. Current output: 300 Ω max.	
Zero Adjustment	Approx. \pm 2% of span (Adjustable by front-access trimmer)	
Span Adjustment	Approx. \pm 2% of span (Adjustable by front-access trimmer)	

PERFORMANCE

Accuracy Rating	\pm 0.1%/F.S (25°C \pm 5°C)
Temperature Effect	\pm 0.2% of span @10°C variance
Response Time	85msec max. (0 \rightarrow 90%) @100% step input
CMRR	100dB min. (500V AC, 50/60Hz)
Isolation	Across Input, Out-1, Out-2 and Power input mutually
Insulation Resistance	100M Ω min. (@500V DC) Across Input, Out-1, Out-2 and Power input mutually
Dielectric Strength	Across Input and other ports: 1500V AC for 1 minute Across Out-1, Out-2, Power input mutually: 500V AC for 1 minute
Surge Withstand Capability	Tested for ANSI/IEEE C37.90.1-1989
Operating Environment	Ambient temperature: 0~55°C Humidity: 90% max. (Non-condensation)
Storage Temperature	-10~60°C

PHYSICAL

Installation	Installed on mounting base (RC3900-□□Al)
External Connection	Wired to mounting base (RC3900-□□Al)
Dimension	W19.5 \times H53 \times D84mm
Weight	Approx. 70g


MATERIAL

Housing	ABS Resin (UL94V-0)
PC Board	Glass Fabric, Epoxy Resin (CEM-3)
Anti-humidity Coating	HumiSeal 1A27NS (Polyurethane)

ADDITIONAL

Other Options	Please consult our sales representatives for the availability of the following options before ordering: (Items) (How to specify) Change response frequency $F_c = \square\square\square\text{Hz}$ (Up to 200Hz) Change response time ... $T_c = \square\square\square\text{sec}$ (Up to 2msec @90%)
----------------------	--

TERMINAL ASSIGNMENT



端子	信 号	端子	信 号
①	+ INPUT	⑦	+ OUTPUT 1
②	- INPUT	⑧	- OUTPUT 1
③	N. C.	⑨	+ OUTPUT 2
④	N. C.	⑩	- OUTPUT 2
⑤	N. C.	⑪	+ POWER DC24V
⑥	N. C.	⑫	- POWER DC24V
		⑬	N. C.
		⑭	N. C.
		⑮	F. G.
		⑯	N. C.

BLOCK DIAGRAM

