

PCAN-PCI

CAN Interface for PCI

The PCAN-PCI card enables the connection of a PC with PCI slots to CAN networks.

The card is available as a single or dual-channel version. The opto-decoupled versions also guarantee galvanic isolation of up to 500 Volts between the PC and the CAN sides.

The package is also supplied with the CAN monitor PCAN-View for Windows and the programming interface PCAN-Basic.



D-Sub	Pin	Pin assignment
	1	Not connected / optional +5V
	2	CAN-L
	3	GND
	4	Not connected
	5	Not connected
	6	GND
	7	CAN-H
	8	Not connected
	9	Not connected / optional +5V

Specifications

- ___ PC plug-in card for PCI slots
- ___ 1 or 2 High-speed CAN channels (ISO 11898-2)
- ___ Bit rates from 5 kbit/s up to 1 Mbit/s
- ___ Compliant with CAN specifications 2.0A (11-bit ID) and 2.0B (29-bit ID)
- ___ CAN bus connection via D-Sub, 9-pin (in accordance with CiA® 106)
- ___ NXP SJA1000 CAN controller, 16 MHz clock frequency
- ___ NXP PCA82C251 CAN transceiver
- ___ 5-Volt supply to the CAN connection can be connected through a solder jumper, e.g., for external bus converter
- ___ Galvanic isolation on the CAN connection up to 500 V, separate for each CAN channel (only for IPEH-002066 and IPEH-002067)
- ___ Extended operating temperature range from -40 to +85 °C (-40 to +185 °F)

Ordering information

Designation	Part No.
PCAN-PCI Single Channel	IPEH-002064
PCAN-PCI Dual Channel	IPEH-002065
PCAN-PCI Single Channel opto-decoupled	IPEH-002066
PCAN-PCI Dual Channel opto-decoupled	IPEH-002067

Scope of supply

- ___ Plug-in card PCAN-PCI
- ___ Device drivers for Windows 11 (x64), 10 (x64), and Linux
- ___ CAN monitor PCAN-View for Windows (details on page 94)
- ___ Programming interface PCAN-Basic for developing applications with CAN connection (details on page 80)
- ___ Programming interfaces for standardized protocols from the automotive sector
- ___ Manual in PDF format